

At the heart of the image TM



COOLPIX. STYLE brilliance made beautiful

Sculpted elegance meets startling speed.





Key Features

8.1 Megapixels for stunning prints as large as 16 x 20 inches

3x Optical Zoom-Nikkor Glass Lens – Nikkor optics provide exceptional pictures

VR Optical Image Stabilization minimizes the effect of camera shake

Incredible, Bright 2.5-inch High Resolution LCD makes it easy to compose and share your pictures

High Response – power-up within 0.7 seconds and shutter delay of only .005 seconds

Auto adjusts up to ISO 2000 - keep shooting, even in low light

All New Stylish, All Metal Design slips right into your shirt pocket or purse!

In-Camera Red-Eye Fix™ automatically fixes most instances of red-eye in the camera. You may never see red-eye again

Face-Priority AF – Nikon's face-finding technology that automatically focuses on up to 12 faces

D-Lighting rescues dark or backlit images by improving brightness and detail where needed

COOLPIX. S510

VR Optical Image Stabilization





with vibration reduction

Nikon's VR Optical Image Stabilization system compensates for camera shake to produce clearer, sharper results in lower light or unsteady conditions. Active full time, VR's stabilizing effects also aid in smooth, easy framing and shooting.



Quality, compact stainless steel body



From the solid feel and comfortable wraparound grip of its ultra compact stainless steel body to its large, easy-access control buttons and 2.5-inch high-resolution LCD monitor, the COOLPIX S510 is a joy to carry and to take pictures with

Fast and Built-to-Last

All functions are optimized for immediate response, freeing you to capture special moments as you experience them. The COOLPIX S510 powers up within 0.7 seconds, and the shutter releases in 0.005 seconds.

ISO 2000 Capability





Better pictures

Light sensitivity range up to ISO 2000 with manual control or auto control (up to ISO 1000) creates new opportunities to take sharper, more natural looking photos in lower lighting conditions, or to capture fast-moving subjects with outstanding clarity.

Nikon In-Camera Innovations Makes taking great pictures easy!





In-Camera Red-EyeFix™ This in-camera feature automatically fixes most typical occurrences of red-eve.







Face-Priority AF Automatically finds and focuses on up to 12 faces to ensure superb portraits with clear, crisp focus.



COOLPIX. S510

Digital Camera Specifications







stabilization

in lower light

Effective pixels: 8.1 million

1/2.5-in. CCD; total pixels: approx. 8.29 million Image sensor:

3x Zoom-NIKKOR; 5.7-17.1mm (35mm [135] format picture angle: Lens:

35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x

(35mm [135] format picture angle: 420mm)

50cm (1 ft. 7.7 in.) to infinity (∞), Macro close-up mode: Focus range:

(from lens) 15cm (5.9 in.) to infinity (∞)

Monitor: 2.5-in., 230,000-dot, TFT LCD with wide viewing angle and

anti-reflection coating

Storage media: Internal memory (approx. 52 MB), SD/SDHC memory card compatible

3246 x 2448 (High: 3264*/Normal: 3264), 2592 x 1944 Image size:

(Normal: 2592), 2048 x 1536 (Normal: 2048), 1024 x 768 (PC: 1024),

640 x 480 (TV: 640), 3200 x 1800 (16:9)

Vibration Reduction: VR Optical Image Stabilization (VR)

ISO sensitivity: ISO 64, 100, 200, 400, 800, 1600, 2000,

Auto (auto gain ISO 64-1000)

Interface:

Power sources: Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter

EH-62D (optional)

Battery life: Approx. 170 shots with EN-EL10 battery (based on CIPA standard)

Approx. 88 x 51 x 22 mm (3.5 x 2.0 x 0.9 in.) **Dimensions:**

excluding projections

Weight: Approx. 125 g (4.4 oz.) without battery and SD memory card

Rechargeable Li-ion Battery EN-EL10, Battery Charger MH-63, Supplied accessories*:

USB Cable UC-E6, Audio Video Cable EG-CP14, Strap,

*Supplied accessories may differ by country or area.

COOLPIX Software Suite CD-ROM

Optional accessories: AC Adapter EH-62D

System Requirements:

Macintosh: Mac OS X version 10.3.9, 10.4.x OS

Windows: WindowsVista (32bit), Windows XP Home Edition/Professional pre-installed models

Note: CD-ROM drive required for installation. Only built-in USB ports

are supported

Microsoft®, Windows® and Windows VistaTM are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh®, Mac® OS and QuickTime® are either registered trademarks or trademarks of Apple Inc. in the United States and/or other countries. The SDHC logo is a trademark. ImageLink and ImageLink print system logo are trademarks of Eastman Kodak Company. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. The FotoNation logo is a trademark. The FotoConnect logo is a trademark. Products and brand names are trademarks or registered trademarks of their respective companies.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. August 2007 @2007 NIKON INC.



























